



**ARIB STD-T104-36.307 V11.17.0**

**Evolved Universal Terrestrial Radio  
Access (E-UTRA); Requirements on  
User Equipments (UEs) supporting  
a release-independent frequency  
band**

**(Release 11)**

# 3GPP TS 36.307 V11.17.0 (2016-09)

---

*Technical Specification*

## **3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements on User Equipments (UEs) Supporting a release-independent frequency band (Release 11)**



The present document has been developed within the 3<sup>rd</sup> Generation Partnership Project (3GPP™) and may be further elaborated for the purposes of 3GPP. The present document has not been subject to any approval process by the 3GPP Organizational Partners and shall not be implemented. This Specification is provided for future development work within 3GPP only. The Organizational Partners accept no liability for any use of this Specification. Specifications and reports for implementation of the 3GPP™ system should be obtained via the 3GPP Organizational Partners' Publications Offices.

---

Keywords

---

LTE, radio

**3GPP**

Postal address

---

3GPP support office address

---

650 Route des Lucioles - Sophia Antipolis  
Valbonne - FRANCE  
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Internet

---

<http://www.3gpp.org>

---

**Copyright Notification**

---

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© 2016, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).  
All rights reserved.

UMTS™ is a Trade Mark of ETSI registered for the benefit of its members  
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners  
LTE™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners  
GSM® and the GSM logo are registered and owned by the GSM Association

---

# Contents

Foreword.....	4
1 Scope.....	5
2 References.....	5
3 Definitions and Abbreviations .....	5
3.1 Definitions .....	5
3.2 Abbreviations.....	5
3A General .....	5
3A.1 Operating bands and CA .....	5
3A.2 Other features.....	7
4 – 292 Void.....	7
<b>Annex A (informative): Frequency arrangement for overlapping operating bands.....</b>	<b>8</b>
<b>Annex B (normative): Common Requirements.....</b>	<b>9</b>
B.1 Purpose of annex .....	9
B.2 Common RRM requirements .....	9
B.2.1 Common RRM requirements for a band independent of release .....	9
B.2.2 Common RRM requirements for an intra-band contiguous CA configuration .....	10
B.2.3 Common RRM requirements for an intra-band non-contiguous CA configuration.....	10
B.2.4 Common RRM requirements for an inter-band CA configuration .....	11
B.3 Common UE performance requirements.....	11
B.3.1 Void .....	11
B.3.2 Common UE performance requirements and tests for different CA configurations and combination sets .....	11
B.3.3 Void .....	12
B.3.4 Void .....	12
B.4 Common UE RF requirements.....	12
B.4.1 Common UE RF requirements for a band independent of release.....	12
B.4.2 Common UE RF requirements for an intra-band contiguous CA configuration.....	13
B.4.3 Common UE RF requirements for an inter-band CA configuration .....	14
B.4.4 Common UE RF requirements for an inter-band CA configuration including an operating band without uplink band .....	15
B.4.5 Common UE RF requirements for an intra-band non-contiguous CA configuration .....	15
<b>Annex C (informative): Change history .....</b>	<b>17</b>

---

## Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

# 1 Scope

The present document specifies requirements on UEs supporting a frequency band and inter-band/intra-band CA configurations that are independent of release. The present document also defines requirements for 4RX antenna port requirements that are independent of release.

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 36.101 (Release 11): "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) Radio Transmission and Reception".
- [3] 3GPP TS 36.133 (Release 11): "Evolved Universal Terrestrial Radio Access (E-UTRA); Requirements for Support of Radio Resource Management".
- [4] 3GPP TS 36.101 (Release 10): "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) Radio Transmission and Reception".
- [5] 3GPP TS 36.101 (Release 12): "Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) Radio Transmission and Reception".

---

# 3 Definitions and Abbreviations

## 3.1 Definitions

For the purposes of the present document, the terms and definitions given in [1] apply.

## 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

---

## 3A General

### 3A.1 Operating bands and CA

TSG-RAN has agreed that the standardisation of new features listed in Tables 3A.1-1, 3A.1-2, 3A-3 and, 3A.1-4 are independent of a release. UE conforming earlier release than when the feature was introduced into the specifications shall comply with RRM-, demodulation- and RF-requirements as specified in the Annex-B2, Annex-B3 and, Annex-

B4 of TS 36.307 in the release that the feature was introduced. The applicable UE Categories are specified in TS 36.306 according to the release to which the UE conforms.

**Table 3A.1-1: E-UTRA operating bands and UE power class**

Feature	Duplex-mode	Release independent from
Operating bands, band number <= 64, Power Class 3	FDD, TDD	8
Operating bands, band number > 64, Power Class 3	FDD, TDD	9
Asymmetric operating bands, Power Class 3	FDD	10
Operating bands, band number <= 64, Power Class 1	FDD	10

**Table 3A.1-2: Intra-band contiguous CA**

CA feature	DL/UL	CA BW Class	Duplex-mode	Release independent from
Intra-band contiguous CA	DL	B	FDD	10
		C	FDD, TDD	10
		D	TDD	10
			TDD	11
	E	TDD	11	
	UL	B	FDD	10
		C	FDD, TDD	10

**Table 3A.1-3: Inter-band CA**

CA feature	DL/UL	number of bands	CA BW Classes	Duplex-mode	Release independent from
Inter-band CA	DL	2	A, B, C	FDD, TDD	10
			A, B, C, D	FDD, TDD	11
		3	A	FDD, TDD	10
			A, B, C	FDD, TDD	11
		4	A, C	FDD, TDD	11
	UL	2	A, C	FDD, TDD	11

**Table 3A.1-4: Intra-band non-contiguous CA**

CA type	DL/UL	number of sub-blocks	CA BW Classes	Duplex-mode	Release independent from
Intra-band non-contiguous CA	Downlink	2	A, C, D	FDD, TDD	11
	Uplink	2	A	FDD	11

For example, Band 19 is contained in the Release 9 specifications. In order to implement a UE conforming to Release 8 but supporting Band 19, it is necessary for the UE to additionally conform to some parts of the Release 9 specifications, such as the radio frequency and radio resource management requirements for the Band 19.

For another example on carrier aggregations, CA configuration CA\_1A-19A is contained in the Release 11 specifications. In order to implement a UE conforming to Release 10 but supporting the CA configuration CA\_1A-19A, it is necessary for the UE to additionally conform to some parts of the Release 11 specifications, such as the radio frequency and radio resource management requirements for the CA configuration CA\_1A-19A.

All frequency bands are fully specified in this release of the specifications. The present document does not contain any requirements for UEs supporting frequency bands independent of release.

NOTE: See NOTE in clause 4.4 in [2].

## 3A.2 Other features

Features other than frequency bands and CA configurations can also be implemented independent of release, as listed in Tables 3A.2-1.

4 Rx compliant Rel-10 UE that supports 4 Rx reception and declares compliance to 4 Rx requirements shall comply with RF requirements, UE demodulation and CSI requirements as specified in the Annex-C.1 and Annex-C.2 of TS 36.307 in the release that the feature was introduced.

**Table 3A.2-1: Other feature**

<b>Feature</b>	<b>Release independent from</b>
4RX	10

---

4 – 292 Void



## Annex A (informative): Frequency arrangement for overlapping operating bands

The following information is provided in order to assist a UE derive the DL EARFCN and UL EARFCN in a multi-band environment, in which multiple overlapping operating bands may be indicated in the fields *freqBandIndicator* and *multiBandInfoList* of SIB1.

The overlapping bands, independent of release, which may be indicated in a cell are shown in Table A-1 for applicable E-UTRA bands. The DL EARFCN and UL EARFCN are derived according to [2].

**Table A-1: Overlapping bands (multi-band environments) for each E-UTRA band**

E-UTRA Operating Band	Overlapping E-UTRA operating bands	Duplex Mode
2	25	FDD
3	9	FDD
4	10	FDD
5	18, 19, 26	FDD
9	3	FDD
10	4	FDD
12	17	FDD
17	12	FDD
18	5, 26, 27	FDD
19	5, 26	FDD
25	2	FDD
26	5, 18, 19, 27	FDD
27	18, 26	FDD
33	39	TDD
38	41	TDD
39	33	TDD
41	38	TDD

## Annex B (normative): Common Requirements

### B.1 Purpose of annex

The purpose of Annex B is to group the requirements that are common for several bands or CA configurations in this specification and use the common tables as references.

### B.2 Common RRM requirements

#### B.2.1 Common RRM requirements for a band independent of release

The requirements and test cases listed in Table B.2.1-1 are specified in [3].

**Table B.2.1-1: Common RRM requirements for a band independent of release**

Section / Clause	Description
4 <sup>Note 1</sup>	E-UTRAN RRC_IDLE state mobility
5	E-UTRAN RRC_CONNECTED state mobility
6 <sup>Note 2</sup>	RRC Connection Mobility Control
7 <sup>Note 3</sup>	Timing and signalling characteristics
8 <sup>Note 4</sup>	UE Measurements Procedures in RRC_CONNECTED State
9 <sup>Note 5</sup>	Measurements performance requirements for UE
A.4 <sup>Note 1</sup>	E-UTRAN RRC_IDLE state
A.5	E-UTRAN RRC_CONNECTED Mode Mobility
A.6 <sup>Note 2</sup>	RRC Connection Control
A.7 <sup>Note 3</sup>	Timing and Signalling Characteristics
A.8 <sup>Note 4</sup>	UE Measurements Procedures
A.9 <sup>Note 5</sup>	Measurement Performance Requirements
<p>NOTE 1: All requirements and the corresponding test cases shall apply, except:</p> <ul style="list-style-type: none"> <li>- for supporting the corresponding band in Rel-9 and below: clause 4.3 (Minimization of Drive Tests).</li> </ul> <p>NOTE 2: All requirements and the corresponding test cases shall apply, except:</p> <ul style="list-style-type: none"> <li>- for supporting the corresponding band in Rel-8: clauses 6.3 (RRC Connection Release with Redirection), 6.4 (CSG Proximity Indication for E-UTRAN and UTRAN).</li> </ul> <p>NOTE 3: All requirements and corresponding test cases shall apply, except those defined in sections 7.4 and 7.5.</p> <p>NOTE 4: All requirements and corresponding test cases shall apply, except:</p> <ul style="list-style-type: none"> <li>- for supporting the corresponding band in Rel-8: clauses 8.1.2.5 (E-UTRAN OTDOA Intra-Frequency RSTD Measurements), 8.1.2.6 (E-UTRAN Inter-Frequency OTDOA Measurements), 8.1.2.7 (E-UTRAN E-CID Measurements).</li> </ul> <p>NOTE 5: All requirements and corresponding test cases shall apply, except:</p> <ul style="list-style-type: none"> <li>- for supporting the corresponding band in Rel-8: clauses 9.1.9 (UE Rx-Tx time difference), 9.1.10 (Reference Signal Time Difference).</li> </ul> <p>NOTE 6: All requirements and test cases in this table shall apply, except those defined for: carrier aggregation; measurements under time-domain measurement resource restriction with or without CRS assistance information, in addition to the exceptions listed above.</p>	

## B.2.2 Common RRM requirements for an intra-band contiguous CA configuration

The requirements and test cases listed in Table B.2.2-1 are specified in [3].

**Table B.2.2-1: Common RRM requirements for a single-band CA configuration independent of release**

Section / Clause	Description
7.1	UE transmit timing
7.7	SCell Activation and Deactivation Delay for E-UTRA Carrier Aggregation
7.8	Interruptions with Carrier Aggregation
8.2	Capabilities for Support of Event Triggering and Reporting Criteria
8.3	Measurements for E-UTRA carrier aggregation
8.4	OTDOA RSTD Measurements for E-UTRAN carrier aggregation
9.1.11	Carrier aggregation measurement accuracy
9.1.12	Reference Signal Time Difference (RSTD) Measurement Accuracy Requirements for Carrier Aggregation
A.7	Timing and Signalling Characteristics
A.8	UE Measurements Procedures
A.9	Measurement Performance Requirements
NOTE: Only requirements and test cases defined for intra-band contiguous carrier aggregation shall apply.	

## B.2.3 Common RRM requirements for an intra-band non-contiguous CA configuration

The requirements and test cases listed in Table B.2.3-1 are specified in [3].

**Table B.2.3-1: Common RRM requirements for a single-band CA configuration independent of release**

Section / Clause	Description
7.1	UE transmit timing
7.7	SCell Activation and Deactivation Delay for E-UTRA Carrier Aggregation
7.8	Interruptions with Carrier Aggregation
8.2	Capabilities for Support of Event Triggering and Reporting Criteria
8.3	Measurements for E-UTRA carrier aggregation
8.4	OTDOA RSTD Measurements for E-UTRAN carrier aggregation
9.1.11	Carrier aggregation measurement accuracy
9.1.12	Reference Signal Time Difference (RSTD) Measurement Accuracy Requirements for Carrier Aggregation
A.7	Timing and Signalling Characteristics
A.8	UE Measurements Procedures
A.9	Measurement Performance Requirements
NOTE: Only requirements and test cases defined for intra-band non-contiguous carrier aggregation shall apply.	

Editor's note: references to this section are to be revisited when intra-band non-contiguous CA requirements are finalized in TS 36.101.

## B.2.4 Common RRM requirements for an inter-band CA configuration

The requirements and test cases listed in Table B.2.4-1 are specified in [3].

**Table B.2.4-1: Common RRM requirements for a band-combination CA configuration**

Section / Clause	Description
7.1	UE transmit timing
7.7	SCell Activation and Deactivation Delay for E-UTRA Carrier Aggregation
7.8	Interruptions with Carrier Aggregation
8.2	Capabilities for Support of Event Triggering and Reporting Criteria
8.3	Measurements for E-UTRA carrier aggregation
8.4	OTDOA RSTD Measurements for E-UTRAN carrier aggregation
9.1.11	Carrier aggregation measurement accuracy
9.1.12	Reference Signal Time Difference (RSTD) Measurement Accuracy Requirements for Carrier Aggregation
A.7	Timing and Signalling Characteristics
A.8	UE Measurements Procedures
A.9	Measurement Performance Requirements
NOTE: Only requirements and test cases defined for inter-band carrier aggregation shall apply.	

---

## B.3 Common UE performance requirements

### B.3.1 Void

**Table B.3.1-1: Void**

### B.3.2 Common UE performance requirements and tests for different CA configurations and combination sets

The requirements and test cases listed in Table B.3.2-1 are specified in [2].

**Table B.3.2-1: Common UE performance requirements and tests for different CA configurations and combination sets**

Section / Clause	Description
8.2.1.1.1	Single-antenna port performance (FDD)
8.2.2.1.1	Single-antenna port performance (TDD)
8.2.1.3.1	Open-loop spatial multiplexing performance - Minimum Requirement 2 Tx Antenna Port (FDD)
8.2.2.3.1	Open-loop spatial multiplexing performance - Minimum Requirement 2 Tx Antenna Port (TDD)
8.2.1.3.1A	Open-loop spatial multiplexing performance - Soft buffer management test (FDD)
8.2.2.3.1A	Open-loop spatial multiplexing performance - Soft buffer management test (TDD)
8.2.1.4.3	Closed-loop spatial multiplexing performance - Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port (FDD)
8.2.2.4.3	Closed-loop spatial multiplexing performance - Minimum Requirement Multi-Layer Spatial Multiplexing 4 Tx Antenna Port (TDD)
8.2.1.7	Carrier aggregation with power imbalance (FDD)
8.2.2.7	Carrier aggregation with power imbalance (TDD)
8.2.1.8	Intra-band non-contiguous carrier aggregation with timing offset (FDD)
8.7.1	Sustained downlink data rate provided by lower layers (FDD)
8.7.2	Sustained downlink data rate provided by lower layers (TDD)
9.6.1.1	Additional requirements for carrier aggregation - Periodic reporting on multiple cells (Cell Specific Reference symbols) (FDD)
9.6.1.2	Additional requirements for carrier aggregation - Periodic reporting on multiple cells (Cell Specific Reference symbols) (TDD)
Note 1:	The applicability of requirements for different CA configurations and bandwidth combination sets is specified in Section 8.1.2.3 and 9.1.1.2 in [2].
Note 2:	The test coverage for different number of component carriers is defined in 8.1.2.4 in [5].

### B.3.3 Void

**Table B.3.3-1: Void**

### B.3.4 Void

---

## B.4 Common UE RF requirements

### B.4.1 Common UE RF requirements for a band independent of release

The requirements and test cases listed in Table B.4.1-1 are specified in [2].

Table B.4.1-1: Common UE RF requirements for a band independent of releaseSection / Clause	Description
5.5	Operating bands
5.6	Channel bandwidth
5.7	Channel arrangement
6.2	Transmit power
6.3	Output power dynamics
6.5 (NOTE)	Transmit signal quality
6.6	Output RF spectrum emissions
6.7	Transmit intermodulation
7.3	Reference sensitivity power level
7.4	Maximum input level
7.5	Adjacent Channel Selectivity (ACS)
7.6	Blocking characteristics
7.7	Spurious response
7.8	Intermodulation characteristics
7.9	RX spurious emissions
NOTE: Requirements in section 6.5.2.2.1 and 6.5.2.3.1 as specified in [4] apply	

## B.4.2 Common UE RF requirements for an intra-band contiguous CA configuration

The requirements and test cases listed in Table B.4.2-1 are specified in [2].

**Table B.4.2-1: Common UE RF requirements for an intra-band contiguous CA configuration independent of release**

Section / Clause	Description
5.5A	Operating bands for CA
5.6A	Channel bandwidths per operating band for CA
5.7.1A	Channel spacing for CA
5.7.2A	Channel raster for CA
5.7.4A	TX–RX frequency separation for CA
6.2.2A	UE maximum output power for CA
6.2.3A	UE maximum output power for modulation/channel bandwidth for CA
6.2.4A	UE maximum output power with additional requirements for CA
6.2.5A	Configured transmitted power for CA
6.3.2A	UE Minimum output power for CA
6.3.3A	UE Transmit OFF power for CA
6.3.4A	ON/OFF time mask for CA
6.3.5A	Power control for CA
6.5.1A	Frequency error for CA
6.5.2A	Transmit modulation quality for CA
6.6.1A	Occupied bandwidth for CA
6.6.2.1A	Spectrum emission mask for CA
6.6.2.2A	Additional Spectrum Emission mask for CA
6.6.2.3.2A	UTRA ACLR for CA
6.6.2.3.3A	E-UTRA ACLR for CA
6.6.3.1A	Minimum requirements for CA
6.6.3.2A	Spurious emission band UE co-existence for CA
6.6.3.3A	Additional spurious emissions for CA
6.7.1A	Minimum requirement for CA
7.3.1A	Reference sensitivity for CA
7.4.1A	Maximum input level for CA
7.5.1A	Adjacent Channel Selectivity (ACS) for CA
7.6.1.1A	In-band blocking for CA
7.6.2.1A	Out-of-band blocking for CA
7.6.3.1A	Narrow band blocking for CA
7.7.1A	Spurious response for CA
7.8.1A	Wideband intermodulation for CA
7.10.1A	Receiver response for CA

### B.4.3 Common UE RF requirements for an inter-band CA configuration

The requirements and test cases listed in Table B.4.3-1 are specified in [2].

**Table B.4.3-1: Common UE RF requirements for an inter-band CA configuration independent of release**

Section / Clause	Description
5.5A	Operating bands for CA
5.6A.1	Channel bandwidths per operating band for CA
5.7.2A	Channel raster for CA
6.2.2A	UE maximum output power for CA
6.2.3A	UE maximum output power for modulation/channel bandwidth for CA
6.2.5	Configured transmitted power
7.3.1A	Reference sensitivity for CA
7.4.1A	Maximum input level for CA
7.5.1A	Adjacent Channel Selectivity (ACS) for CA
7.6.1.1A	In-band blocking for CA
7.6.2.1A	Out-of-band blocking for CA
7.6.3.1A	Narrow band blocking for CA
7.7.1A	Spurious response for CA
7.8.1A	Wideband intermodulation for CA

#### B.4.4 Common UE RF requirements for an inter-band CA configuration including an operating band without uplink band

The requirements and test cases listed in Table B.4.4-1 are specified in [2].

**Table B.4.4-1: Common UE RF requirements for an inter-band CA configuration including an operating band without uplink band independent of release**

Section / Clause	Description
5.5	Operating bands
5.5A	Operating bands for CA
5.6A.1	Channel bandwidths per operating band for CA
5.7	Channel arrangement
6.2.2A	UE maximum output power for CA
6.2.3A	UE maximum output power for modulation/channel bandwidth for CA
6.2.5	Configured transmitted power
7.3.1A	Reference sensitivity for CA
7.4.1A	Maximum input level for CA
7.5.1A	Adjacent Channel Selectivity (ACS) for CA
7.6.1.1A	In-band blocking for CA
7.6.2.1A	Out-of-band blocking for CA
7.6.3.1A	Narrow band blocking for CA
7.7.1A	Spurious response for CA
7.8.1A	Wideband intermodulation for CA

#### B.4.5 Common UE RF requirements for an intra-band non-contiguous CA configuration

The requirements and test cases listed in Table B.4.5-1 are specified in [2].



**Table B.4.5-1: Common UE RF requirements for an intra-band non-contiguous CA configuration independent of release**

<b>Section / Clause</b>	<b>Description</b>
5.5A	Operating bands for CA
5.6A1	Channel bandwidths per operating band for CA
5.7.2A	Channel raster for CA
6.2.2A	UE maximum output power for CA
6.2.3A	UE maximum output power for modulation/channel bandwidth for CA
7.3.1A	Reference sensitivity for CA
7.4.1A	Maximum input level for CA
7.5.1A	Adjacent Channel Selectivity (ACS) for CA
7.6.1.1A	In-band blocking for CA
7.6.2.1A	Out-of-band blocking for CA
7.6.3.1A	Narrow band blocking for CA
7.7.1A	Spurious response for CA
7.8.1A	Wideband intermodulation for CA

## Annex C (informative): Change history

**Table C.1: Change History**

Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
11-2009	RP#46	RP-091141				TS36.307 V0.1.0 approved by RAN (Originally in R4-095022)	0.1.0
02-2010	R4#54	R4-100419				For release 9 version, replace sections 4 to 6 as 'Void' and add a new void section as section 7.	0.2.0
03-2010	RP#47	RP-100162				TS36.307 v1.0.0 for approval	1.0.0
03-2010	RP#47	RP-100162				Approved by RAN	9.0.0
09-2010	RP-49	RP-100927	2			CR LTE_TDD_2600_US spectrum band definition additions to TS 36.307 V900	9.1.0
						Correction of section numbering	9.1.1
12-2010	RP-50	RP-101356	008			Band 42 and 43 parameters for UMTS/LTE 3500 (TDD) for TS 36.307	9.2.0
12-2010	RP-50	RP-101361	005			Introduction of L-band in TS 36.307	9.2.0
12-2010	RP-50	RP-101344	016			CR creating the rel-10 of the 36.307 specification	9.3.0
12-2010	RP-50	RP-101356	012			Band 42 and 43 parameters for UMTS/LTE 3500 (TDD) for TS 36.307	9.3.0
12-2010	RP-50					Raised to Rel-10 with no technical change	10.0.0
01-2011						Correction to history table	10.0.1
06-2011	RP-52	RP-110804	015			Add Expanded 1900 MHz Band (Band 25) in 36.307	10.1.0
06-2011	RP-52	RP-110812	022			Add 2GHz S-Band (Band 23) in 36.307 (Rel 10)	10.1.0
09-2011	RP-53	RP-111255	025			Add Band 22 for LTE/UMTS 3500 (FDD) to TS 36.307	10.2.0
03-2012	RP-55	RP-120305	029			Introduction of Band 26/XXVI to TS 36.307	11.0.0
2012-06	RP-56	RP-120789	043			Introduction of CA_1A-19A to TS 36.307	11.1.0
2012-06	RP-56	RP-120793	049			Introduction of APAC700(FDD) into TS 36.307 Rel-11	11.1.0
2012-06	RP-56	RP-120793	053			Introduction of APAC700(TDD) into TS 36.307 Rel-11	11.1.0
2012-06	RP-56	RP-120791	057			Introduction of e850_LB (Band 27) to TS 36.307	11.1.0
2012-09	RP-57	RP-121335	059			Introduction of CA_1A-21A to TS 36.307	11.2.0
2012-09	RP-57	RP-121295	070r1			Relation between EARFCN for overlapping bands with multiple FBI indication	11.2.0
2012-09	RP-57	RP-121338	072			36.307 CR for LTE_CA_B7	11.2.0
2012-09	RP-57	RP-121337	073			TS 36.307 CR for CA_38	11.2.0
2012-09	RP-57	RP-121327	074			Introduction of CA_B7_B20 in 36.307	11.2.0
2012-09	RP-57	RP-121329	075			Introduction of CA band combination Band3 + Band5 to TS 36.307	11.2.0
2012-09	RP-57	RP-121331	076			Introduction of CA_3A-20A to TS 36.307	11.2.0
2012-09	RP-57	RP-121334	077			Add requirements for inter-band CA of B_1-18 in TS36.307	11.2.0
2012-09	RP-57	RP-121333	078			Introduction of CA_8_20 RF requirements into TS36.307	11.2.0
2012-09	RP-57	RP-121324	079			Introduction of CA_B3_B7 in 36.307	11.2.0
2012-12	RP-58	RP-121890	086			Introduction of CA_4A-5A into 36.307	11.3.0
2012-12	RP-58	RP-121889	088			Introduction of CA band combination Band4 + Band13 to TS 36.307 (Rel-11)	11.3.0
2012-12	RP-58	RP-121896	091			Introduction of Band 5 + Band 17 inter-band CA configuration into 36.307	11.3.0
2012-12	RP-58	RP-121884	092			Introduction of CA_3A-8A to TS 36.307	11.3.0
2012-12	RP-58	RP-121894	093			Introduction of CA_B5_B12 in 36.307	11.3.0
2012-12	RP-58	RP-121887	095			Introduction of CA_4-12 into TS 36.307 (Rel-11)	11.3.0
2012-12	RP-58	RP-121882	097			[Rel-11] Introduction of inter-band CA_11-18 into TS36.307	11.3.0
2012-12	RP-58	RP-121861	099			Release-independent implementation of carrier aggregation configuration CA_4-7	11.3.0
2012-12	RP-58	RP-121901	101			Introduction of Band 29	11.3.0
2012-12	RP-58	RP-121718	0102			Introduction of CA band combination Band2 + Band17 to TS 36.307 (Rel-11)	11.3.0
2012-12	RP-58	RP-121720	0104			Introduction of CA band combination Band4 + Band17 to TS 36.307 (Rel-11)	11.3.0

2013-06	RP-60	RP-130771	107r1		Introduction of CA 1+8 into TS36.307(Rel-11)	11.4.0
2013-06	RP-60	RP-130782	110r1		Introduction of LTE Advanced inter-band Carrier Aggregation of Band 3 and Band 28 to TS 36.307 Rel-11	11.4.0
2013-06	RP-60	RP-130785	113		Introduction of LTE Advanced inter-band Carrier Aggregation of Band 23 and Band 29 to TS 36.307 (Rel-11)	11.4.0
2013-06	RP-60	RP-130779	116		Introduction of LTE Advanced inter-band Carrier Aggregation of Band 3 and Band 26 to TS 36.307 (Rel-11)	11.4.0
2013-06	RP-60	RP-130777	119		Introduction of CA_3A-19A to TS 36.307	11.4.0
2013-06	RP-60	RP-130783	122		Introduction of CA_19A-21A to TS 36.307	11.4.0
2013-06	RP-60	RP-130787	128		Introduction of CA_4A-4A into 36.307 Rel-11	11.4.0
2013-06	RP-60	RP-130775	130		Introduction of CA_2A-13A to TS 36.307	11.4.0
2013-06	RP-60	RP-130791	135r1		Introduction of Band 30	11.4.0
2013-06	RP-60	RP-130790	142		Introduction of LTE 450 into TS 36.307 R11	11.4.0
09-2013	RP-61	RP-131300	152		36.307 CR for LTE_CA_C_B3 (Rel-11)	11.5.0
09-2013	RP-61	RP-131303	155		Band 31 release independence for UE demodulation performance	11.5.0
09-2013	RP-61	RP-131285	158		[Rel-11] Modify requirements for CA_1A-18A in TS36.307	11.5.0
09-2013	RP-61	RP-131296	159		[Rel-11] Add requirements for CA_1A-26A into TS36.307	11.5.0
09-2013	RP-61	RP-131297	162		Introduction of CA_2A-4A to TS 36.307	11.5.0
09-2013	RP-61	RP-131298	166		Introduction of inter-band CA Band 2+5	11.5.0
12-2013	RP-62	RP-131965	174		Introduction of CA_23A-23A to TS 36.307	11.6.0
12-2013	RP-62	RP-131946	177r1		Introduction of CA band combination Band2 + Band12 to TS 36.307	11.6.0
12-2013	RP-62	RP-131954	180r1		Introduction of CA band combination Band12 + Band25 to TS 36.307	11.6.0
12-2013	RP-62	RP-131959	183		Introduction of LTE_CA_C_B27 to 36.307 (Rel-11)	11.6.0
12-2013	RP-62	RP-131939	189r1		Correction to release independent specification	11.6.0
12-2013	RP-62	RP-131957	191		Introduction of CA_23B to TS 36.307	11.6.0
12-2013	RP-62	RP-131961	193		Introduction of Intra-band non-contiguous CA in band 3 to TS 36.307	11.6.0
12-2013	RP-62	RP-131950	199		Introduction of CA band combination Band5 + Band25 to TS 36.307	11.6.0
12-2013	RP-62	RP-131948	203r1		Introduction of CA band combination B5 + B7 to TS 36.307	11.6.0
12-2013	RP-62	RP-131952	206		Introduction of CA band combination B7 + B28 to TS 36.307	11.6.0
12-2013	RP-62	RP-131925	215		UE performance requirements in release independent specification for CA	11.6.0
12-2013	RP-62	RP-131963	218		Introduction of CA_7A-7A to TS 36.307 Rel-11	11.6.0
12-2013	RP-62	RP-131924	223		Introducing 'General' clause with note referring to note in clause 4.4 in TS36.101, editorial corrections and modifications to Forward and Scope clauses	11.6.0
03-2014	RP-63	RP-140375	231r1		CR on UE performance requirements in release independent specification	11.7.0
03-2014	RP-63	RP-140371	234		Release independence of Band 14 HPUE	11.7.0
03-2014	RP-63	RP-140375	244r1		Correction to release independent specification	11.7.0
03-2014	RP-63	RP-140386	226r2		Introduction of CA band combination Band 3 and Band 27 to TS 36.307	11.7.0
03-2014	RP-63	RP-140188	247		Addition of bandwidth combination set for CA_2A-29A and CA_4A-29A	11.7.0
03-2014	RP-63	RP-140387	196r1		Introduction of CA_39A-41A to TS 36.307	11.7.0
03-2014	RP-63	RP-140388	209r2		Introduction of CA_39C to TS 36.307	11.7.0
06-2014	RP-64	RP-140911	258		Introduction of CA band combination Band 1 and Band 5 to TS 36.307	11.8.0
06-2014	RP-64	RP-140918	299		Correction of Common RRM requirements for CA in release independent specification (Rel-11)	11.8.0
06-2014	RP-64	RP-140926	279		Introduction of Band 20+32 CA	11.8.0
06-2014	RP-64	RP-140931	264		Introduction of CA 1+11 to 36.307 (Rel-11)	11.8.0
06-2014	RP-64	RP-140933	274		Introduction of CA band combination Band 4 and Band 27 to TS 36.307	11.8.0
06-2014	RP-64	RP-140935	277		Addition of bandwidth combination sets for CA_3A-5A, CA_4A-5A, and CA_4A-12A into 36.307	11.8.0

06-2014	RP-64	RP-140938	290		Introduction of CA_2A-2A to TS 36.307 Rel-11	11.8.0
06-2014	RP-64	RP-140940	318		Introduction of LTE_CA_NC_B42 into 36.307	11.8.0
06-2014	RP-64	RP-140942	339		Introduction of CA band combination Band 1 and Band 20 to TS 36.307	11.8.0
06-2014	RP-64	RP-140942	252		Introduction of CA band combination Band 1 and Band 20 to TS 36.307	11.8.0
06-2014	RP-64	RP-140943	346		Introduction of CA band combination CA_41D into TS 36.307 (Rel-11)	11.8.0
06-2014	RP-64	RP-140946	342		Introduction of CA_42C to TS 36.307	11.8.0
06-2014	RP-64	RP-140947	302		Introduction of Band 40D in release independent specification (Rel-11)	11.8.0
06-2014	RP-64	RP-140953	0308		Introduction of a new CA_7C bandwidth combination set into 36.307 (Rel-11)	11.8.0
09-2014	RP-65	RP-141111	0389r1		[Rel-11] Introduction of inter-band CA_18-28 into TS36.307	11.9.0
09-2014	RP-65	RP-141199	0365r1		Introduction of CA_B1_B3_B19 into TS 36.307 (Rel-11)	11.9.0
09-2014	RP-65	RP-141204	0362r1		Introduction of CA_B1_B3 into TS 36.307 (Rel-11)	11.9.0
09-2014	RP-65	RP-141330	0428r1		Introduction of CA_1A-7A into 36.307 (Rel-11)	11.9.0
09-2014	RP-65	RP-141339	0375r2		Introduction of CA_B1_B5_B7 into TS 36.307 (Rel-11)	11.9.0
09-2014	RP-65	RP-141466	0431		Introduction of 3 DL CA for Band 1+7+20	11.9.0
09-2014	RP-65	RP-141527	414r1		CR for 36.307 on CA UE performance requirement in Rel-11	11.9.0
09-2014	RP-65	RP-141538	342r2		Introduction of CA_42C to TS 36.307	11.9.0
09-2014	RP-65	RP-141540	302r2		Introduction of Band 40D in release independent specification (Rel-11)	11.9.0
09-2014	RP-65	RP-141541	412		CR on UE performance requirement for Band 31 for 36.307 Rel-11	11.9.0
09-2014	RP-65	RP-141551	359		Introduction of CA 8+11 to 36.307 (Rel-11)	11.9.0
09-2014	RP-65	RP-141552	378		Introduction of CA_41A-42A to TS 36.307	11.9.0
09-2014	RP-65	RP-141553	380		Introduction of a new bandwidth combination set for CA_25A-25A into 36.307	11.9.0
09-2014	RP-65	RP-141554	417r1		Introduction of requirements for 3DL inter-band carrier aggregation (FDD) and 2DL fallback	11.9.0
09-2014	RP-65	RP-141554	420r1		Introduction of requirements for 3DL inter-band carrier aggregation including Band 30 and 2DL fallback	11.9.0
09-2014	RP-65	RP-141555	383r1		Introduction of 3 Band Carrier Aggregation of Band 1, Band 3 and Band 5 to TS 36.307(Rel.11)	11.9.0
09-2014	RP-65	RP-141556	356r1		Introduction of 3 Band Carrier Aggregation (3DL/1UL) of Band 1, Band 3 and Band 8 to TS 36.307	11.9.0
09-2014	RP-65	RP-141558	401		Introduction of CA band combination Band 1, Band 3 and Band 20 to TS 36.307	11.9.0
09-2014	RP-65	RP-141560	351		Introduction of new CA_40C bandwidth combination set into 36.307	11.9.0
09-2014	RP-65	RP-141561	353r2		CR to 36.307 Rel-11: Introduction of CA_41C-41A and CA_41A-41C and New BW Combination Set for CA_41C	11.9.0
12-2014	RP-66	RP-142142	439r1		UE RF requirements in the release independent spec	11.10.0
12-2014	RP-66	RP-142184	442		Introduction of CA band combinations for dual uplink to TS 36.307 Rel-11	11.10.0
12-2014	RP-66	RP-142182	447		[Rel-11] Introduction of inter-band CA_1-28 into TS36.307	11.10.0
12-2014	RP-66	RP-142189	454		CR for TR 36.307: LTE_CA_B5_B13	11.10.0
12-2014	RP-66	RP-142190	457r2		Introduction of additional band combinations for 3DL inter-band CA	11.10.0
03-2015	RP-67	RP-150387	462		R4-73AH-0112: Correction of UE RF requirements for dual uplink to TS 36.307 Rel-11	11.11.0
03-2015	RP-67	RP-150392	467		CR for 36.307 on CA UE performance requirement in Rel-11	11.11.0
03-2015	RP-67	RP-150388	476r1		Release independent requirements for CA_42C	11.11.0
06-2015	RP-68	RP-151025	0472r3		Introduction of CA_42D to TS 36.307(Rel-11)	11.12.0
06-2015	RP-68	RP-150958	459r1		Introduction of dual uplink CA into 36.307	11.12.0
06-2015	RP-68	RP-150955	481r1		Clean up of requirements of band release independent	11.12.0
06-2015	RP-68	RP-150958	486		CR for CA UE performance tests in 36.307 in Rel-11	11.12.0
06-2015	RP-68	RP-150968	497r2		Release independence CR for 2DL inter-band CA Rel-11	11.12.0
06-2015	RP-68	RP-150972	501r1		Release independence CR for 3DL inter-band CA Rel-11	11.12.0
06-2015	RP-68	RP-150974	504r1		Release independence CR for 4DL inter-band CA Rel-11	11.12.0
06-2015	RP-68	RP-150975	507		Introduction of non-contiguous Carrier Aggregation (CA) in Band 42 for 3DL	11.12.0
09-2015	RP-69	RP-151505	515		Additional bandwidth combination set for LTE Advanced intra-band non-contiguous Carrier Aggregation in Band 4	11.13.0
09-2015	RP-69	RP-151501	518		Introduction of finished 4DL inter-band CAs to TS 36.307	11.13.0
09-2015	RP-69	RP-151476	521r1		Correction of TS 36.307 for release independent	11.13.0
09-2015	RP-69	RP-151498	532		Rel-13 2DL combinations	11.13.0
09-2015	RP-69	RP-151499	536		Rel-13 3DL combinations	11.13.0

09-2015	RP-69	RP-151504	540			Introduction of 3DL/2UL inter-band CA combinations without self-interference issues	11.13.0
12-2015	RP-70	RP-152158	0545aR1			Release independent requirements for CA_42E (Rel-11)	11.14.0
12-2015	RP-70	RP-152160	0547a			Introduction of 4DL NC CA in band42 in 36.307	11.14.0
12-2015	RP-70	RP-152157	0559			Introducing B20 + B67 CA into TS 36.307	11.14.0
12-2015	RP-70	RP-152168	0564			Introduction of intra-band CA_8B to TS 36.307	11.14.0
12-2015	RP-70	RP-152133	0566			[Rel-11] Introduction of dual uplink CA into 36.307	11.14.0
12-2015	RP-70	RP-152164	0567			Introduction of 3DL/2UL inter-band CA combinations with self-interference issues	11.14.0
12-2015	RP-70	RP-152171	0578			Introduction of Band 65	11.14.0
12-2015	RP-70	RP-152133	0591			[Rel-11] Introduction of dual uplink CA into 36.307	11.14.0
12-2015	RP-70	RP-152164	0593			Introduction of 3DL/2UL Inter-band CA for CA_39A-41C and CA_39C-41A	11.14.0
12-2015	RP-70	RP-152164	0599			Introduction of 3DL/2UL inter-band CA_3A-7A-28A in TS36.307 Rel-11	11.14.0
12-2015	RP-70	RP-152162	0602			Introduction of finished 4DL inter-band CAs to TS 36.307	11.14.0
12-2015	RP-70	RP-152170	0605			Introduction of CA_7A-7A BCS1 to TS 36.307	11.14.0
12-2015	RP-70	RP-152173	0610			Introduction of 1447-1467MHz Band into 36.307	11.14.0
12-2015	RP-70	RP-152161	0618			Rel-13 3DL combinations	11.14.0
12-2015	RP-70	RP-152172	0626			Introduction of Band 66	11.14.0
12-2015	RP-70	RP-152165	0629			Introduction of 2 UL and 3 DL mixed inter/intra cases without MSD into 36.307 Rel-11	11.14.0
12-2015	RP-70	RP-152159	0630			Introduction of intra-band non-contiguous CA in Band 41 for 4DL	11.14.0
12-2015	RP-70	RP-152167	0636			Introduction of intra-band CA_5B to TS 36.307	11.14.0
12-2015	RP-70	RP-152169	0638			Introduction of intra-band non-contiguous CA in Band 5	11.14.0
03/2016	RP-71	RP-160480	0653		B	Rel-13 3DL combinations	11.15.0
03/2016	RP-71	RP-160481	0640		B	Introduction of completed R13 4DL inter-band CA's to TS 36.307	11.15.0
03/2016	RP-71	RP-160482	0649		B	Introduction of 5DL/1UL CA combinations into TS 36.307 (Rel-11)	11.15.0
03/2016	RP-71	RP-160483	0645		B	Introduction of Band 68	11.15.0
06/2016	RP-72	RP-161140	680	1	F	CR TS 36.307 REL-11	11.16.0
09/2016	RP-73	RP-161628	695		A	Release 11 36.307 CAT A CR to make Band 41 power class 2 release independent The CRs was not implemented because it was not based on the latest version of the spec.	11.17.0
09/2016	RP-73	RP-161633	701		F	Correction of REL-11 TS 36.307 references	11.17.0