

Attachment 3-2-2

WiMAX ForumTM Mobile System Profile

Release 1.5 TDD Part

Note: This Document is reproduced without any modification with the consent of the WiMAX Forum®, which owns the copyright in them.



WiMAX Forum™ Mobile System Profile Specification

Release 1.5 TDD Specific Part

WMF-T23-002-R015v01

WiMAX Forum Approved

(2009-08-01)

WiMAX Forum Proprietary

Copyright © 2008-2009 WiMAX Forum. All Rights Reserved.

Copyright Notice, Use Restrictions, Disclaimer, and Limitation of Liability.

Copyright 2008-2009 WiMAX Forum. All rights reserved.

The WiMAX Forum owns the copyright in this document and reserves all rights herein. This document is available for download from the WiMAX Forum and may be duplicated for internal use, provided that all copies contain all proprietary notices and disclaimers included herein. Except for the foregoing, this document may not be duplicated, in whole or in part, or distributed without the express written authorization of the WiMAX Forum.

Use of this document is subject to the disclaimers and limitations described below. Use of this document constitutes acceptance of the following terms and conditions:

THIS DOCUMENT IS PROVIDED “AS IS” AND WITHOUT WARRANTY OF ANY KIND. TO THE GREATEST EXTENT PERMITTED BY LAW, THE WiMAX FORUM DISCLAIMS ALL EXPRESS, IMPLIED AND STATUTORY WARRANTIES, INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF TITLE, NONINFRINGEMENT, MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. THE WiMAX FORUM DOES NOT WARRANT THAT THIS DOCUMENT IS COMPLETE OR WITHOUT ERROR AND DISCLAIMS ANY WARRANTIES TO THE CONTRARY.

Any products or services provided using technology described in or implemented in connection with this document may be subject to various regulatory controls under the laws and regulations of various governments worldwide. The user is solely responsible for the compliance of its products and/or services with any such laws and regulations and for obtaining any and all required authorizations, permits, or licenses for its products and/or services as a result of such regulations within the applicable jurisdiction.

NOTHING IN THIS DOCUMENT CREATES ANY WARRANTIES WHATSOEVER REGARDING THE APPLICABILITY OR NON-APPLICABILITY OF ANY SUCH LAWS OR REGULATIONS OR THE SUITABILITY OR NON-SUITABILITY OF ANY SUCH PRODUCT OR SERVICE FOR USE IN ANY JURISDICTION.

NOTHING IN THIS DOCUMENT CREATES ANY WARRANTIES WHATSOEVER REGARDING THE SUITABILITY OR NON-SUITABILITY OF A PRODUCT OR A SERVICE FOR CERTIFICATION UNDER ANY CERTIFICATION PROGRAM OF THE WiMAX FORUM OR ANY THIRD PARTY.

The WiMAX Forum has not investigated or made an independent determination regarding title or noninfringement of any technologies that may be incorporated, described or referenced in this document. Use of this document or implementation of any technologies described or referenced herein may therefore infringe undisclosed third-party patent rights or other intellectual property rights. The user is solely responsible for making all assessments relating to title and noninfringement of any technology, standard, or specification referenced in this document and for obtaining appropriate authorization to use such technologies, technologies, standards, and specifications, including through the payment of any required license fees.

NOTHING IN THIS DOCUMENT CREATES ANY WARRANTIES OF TITLE OR NONINFRINGEMENT WITH RESPECT TO ANY TECHNOLOGIES, STANDARDS OR SPECIFICATIONS REFERENCED OR INCORPORATED INTO THIS DOCUMENT.

IN NO EVENT SHALL THE WiMAX FORUM OR ANY MEMBER BE LIABLE TO THE USER OR TO A THIRD PARTY FOR ANY CLAIM ARISING FROM OR RELATING TO THE USE OF THIS DOCUMENT, INCLUDING, WITHOUT LIMITATION, A CLAIM THAT SUCH USE INFRINGES A THIRD PARTY’S INTELLECTUAL PROPERTY RIGHTS OR THAT IT FAILS TO COMPLY WITH APPLICABLE LAWS OR REGULATIONS. BY USE OF THIS DOCUMENT, THE USER WAIVES ANY SUCH CLAIM AGAINST THE WiMAX FORUM AND ITS MEMBERS RELATING TO THE USE OF THIS DOCUMENT.

The WiMAX Forum reserves the right to modify or amend this document without notice and in its sole discretion. The user is solely responsible for determining whether this document has been superseded by a later version or a different document.

“WiMAX,” “Fixed WiMAX,” “Mobile WiMAX,” “WiMAX Forum,” “WiMAX Certified,” “WiMAX Forum Certified,” the WiMAX Forum logo and the WiMAX Forum Certified logo are trademarks of the WiMAX Forum. Third-party trademarks contained in this document are the property of their respective owners.

TABLE OF CONTENTS

ABSTRACT	9
1. SCOPE	9
2. NORMATIVE REFERENCES	10
3. DEFINITIONS	11
3.1 ABBREVIATIONS	11
3.2 DEFINITIONS OF SYSTEM PROFILES	11
3.3 CONVENTIONS	11
3.3.1 <i>Item column</i>	11
3.3.2 <i>Description column</i>	11
3.3.3 <i>Reference column</i>	11
3.3.4 <i>Status column</i>	11
3.3.5 <i>BS/MS Required column</i>	11
3.3.6 <i>BS/MS Values column</i>	12
3.3.7 <i>Comment column</i>	12
4. PHY PROFILE	13
4.1 PROFILES OF BS AND MS	13
4.1.1 <i>System Parameters</i>	13
4.1.1.1 PHY Mode	13
4.1.1.2 Channel bandwidths and corresponding FFT sizes	13
4.1.1.3 Sampling Factor	13
4.1.1.4 Cyclic Prefix	13
4.1.1.5 Frame Configuration	13
4.1.1.6 TTG/RTG	13
4.1.1.7 Frame and Subframe Parameters	14
4.1.2 <i>Subcarrier Allocation</i>	14
4.1.2.1 DL Subcarrier Allocation	14
4.1.2.2 UL Subcarrier Allocation	14
4.1.2.3 Common SYNC Symbol	14
4.1.2.4 UL Sounding	14
4.1.3 <i>UL Control Channels</i>	15
4.1.3.1 Initial Ranging	15
4.1.3.2 HO Ranging	15
4.1.3.3 Periodic Ranging	15
4.1.3.4 BW Request	15
4.1.3.5 Fast-Feedback/CQI Channel Encoding	15
4.1.3.6 Fast-Feedback/CQI Channel Allocation Method	15
4.1.4 <i>Channel Coding</i>	15
4.1.4.1 Repetition	15
4.1.4.2 Randomization	15
4.1.4.3 Convolutional Code	15
4.1.4.4 Convolutional Turbo Code	15
4.1.4.5 BTC	15
4.1.4.6 LDPC	15
4.1.4.7 Interleaving	15
4.1.5 <i>H-ARQ Support</i>	15
4.1.5.1 Chase Combining	15
4.1.5.2 Incremental Redundancy	15

1	4.1.5.3	ACK Channel	15
2	4.1.6	<i>Control Mechanism</i>	16
3	4.1.6.1	Synchronization.....	16
4	4.1.6.2	Closed-loop Power Control	16
5	4.1.6.3	Open-loop Power Control.....	16
6	4.1.6.4	MS Maximum Transmission Power Limitation Control Using UCD TLV	16
7	4.1.7	<i>Channel Measurement</i>	16
8	4.1.7.1	CINR Measurement.....	16
9	4.1.7.2	RSSI Measurement.....	16
10	4.1.8	<i>Modulation</i>	16
11	4.1.8.1	PRBS (Subcarrier Randomization).....	16
12	4.1.8.2	Downlink	16
13	4.1.8.3	Uplink.....	16
14	4.1.8.4	Pilot Modulation.....	16
15	4.1.8.5	Preamble Modulation	16
16	4.1.8.6	Ranging Modulation.....	16
17	4.1.9	<i>MAP Support</i>	16
18	4.1.9.1	Normal MAP	16
19	4.1.9.2	Compressed MAP.....	16
20	4.1.9.3	Sub-DL-UL MAP.....	16
21	4.1.9.4	H-ARQ MAP Message.....	16
22	4.1.9.5	Extended HARQ IE in the Normal MAP	16
23	4.1.9.6	DL Region Definition.....	16
24	4.1.10	<i>AAS</i>	16
25	4.1.10.1	AAS Zone Support	16
26	4.1.10.2	Supported Permutation in DL.....	16
27	4.1.10.3	Supported Permutation in UL.....	17
28	4.1.10.4	AAS DL Preamble.....	17
29	4.1.10.5	AAS UL Preamble.....	17
30	4.1.10.6	Diversity MAP Scan.....	17
31	4.1.10.7	DL AAS-SDMA Pilots.....	17
32	4.1.10.8	UL AAS-SDMA Pilots.....	17
33	4.1.10.9	AAS Private MAP	17
34	4.1.10.10	AAS-FBCK-REQ/RSP support	17
35	4.1.11	<i>STC/MIMO</i>	17
36	4.1.11.1	Supported Features for DL PUSC	17
37	4.1.11.2	Supported Features for DL FUSC	17
38	4.1.11.3	Supported Features for DL Optional FUSC	17
39	4.1.11.4	Supported Features for DL Optional AMC	17
40	4.1.11.5	Supported Features for DL PUSC-ASCA	17
41	4.1.11.6	Supported Features in UL PUSC.....	17
42	4.1.11.7	Supported Features in UL Optional PUSC.....	17
43	4.1.11.8	Supported Features in UL Optional AMC.....	17
44	4.1.11.9	Closed-Loop MIMO	17
45	4.1.11.10	MIMO Feedback	17
46	4.1.11.11	MIMO Midamble	17
47	4.1.11.12	MIMO Soft-Handover Based Macro-diversity	18
48	4.1.11.13	H-ARQ Downlink Support for MIMO.....	18
49	4.1.11.14	H-ARQ Uplink Support for MIMO	18
50	4.1.12	<i>HO Support in PHY</i>	18
51	4.1.12.1	FBSS.....	18

1	4.1.12.2	MIMO Soft-handover based macro-diversity transmission	18
2	4.1.12.3	UL Macro diversity	18
3	4.2	PERFORMANCE/FIDELITY REQUIREMENTS	18
4	4.2.1	MS Minimum Performance	18
5	4.2.1.1	SSTTG/SSRTG	18
6	4.2.1.2	Max DL Concurrent Bursts	19
7	4.2.1.3	Max Bursts in DL Subframe.....	19
8	4.2.1.4	Max Number of Zones in DL/UL Subframe	19
9	4.2.1.5	Measurement Processes and CQI Channels	19
10	4.2.1.6	Max H-ARQ Bursts in DL/UL Subframe.....	19
11	4.2.2	Transmit Requirements	19
12	4.2.3	Receiver Requirements.....	19
13	4.2.4	Frequency and Time Synchronization Requirements.....	19
14	5.	MAC PROFILE.....	20
15	5.1	PROFILES OF BS AND MS	20
16	5.1.1	PHS	20
17	5.1.2	CS Options	20
18	5.1.3	MAC PDU formats.....	20
19	5.1.4	MAC Support of PHY layer.....	20
20	5.1.4.1	Feedback Mechanism	20
21	5.1.5	Multicast connection.....	20
22	5.1.6	Network Entry	20
23	5.1.7	ARQ.....	20
24	5.1.8	MAC support for H-ARQ.....	20
25	5.1.9	QoS.....	20
26	5.1.10	Data delivery services for mobile network	20
27	5.1.11	Request-Grant mechanism.....	20
28	5.1.12	Neighbor Advertisement	20
29	5.1.13	Scanning and Association.....	20
30	5.1.13.1	Scanning	20
31	5.1.13.2	Scan Reporting Type Support.....	20
32	5.1.13.3	Association	20
33	5.1.13.4	Association Type Support	20
34	5.1.13.5	HO/Scan/Report Trigger Metrics	20
35	5.1.14	MAC layer HO procedures	20
36	5.1.15	HO Optimization.....	20
37	5.1.16	CID and SAID Update	20
38	5.1.17	Fast BS Switching.....	21
39	5.1.18	Macro Diversity Handover	21
40	5.1.19	Sleep Mode.....	21
41	5.1.20	Idle Mode.....	21
42	5.1.21	Expedited Network Re-entry from Idle Mode	21
43	5.1.22	MBS.....	21
44	5.1.23	AAS	21
45	5.1.24	MS's Network Entry issued by BS restart	21
46	5.1.25	NSP Selection.....	21
47	5.1.26	Load Balancing.....	21
48	5.1.27	Location Based Services	21
49	5.1.28	Coexistence Among WiMAX™, Wi-Fi® and Bluetooth® Networks.....	21
50	5.1.29	Capacity Improvements for Feedbacks.....	21

1	5.1.30	Persistent Allocation.....	21
2	5.1.31	Alternative RAT Advertisement.....	21
3	5.2	PARAMETERS	22
4	6.	SECURITY	22
5	6.1	AUTHORIZATION POLICY SUPPORT	22
6	6.2	PKM VERSION SUPPORT	22
7	6.3	PKMv2 AUTHORIZATION POLICY SUPPORT – INITIAL NETWORK ENTRY	22
8	6.4	PKMv2 AUTHORIZATION POLICY SUPPORT – NETWORK RE-ENTRY	22
9	6.5	SUPPORTED CRYPTOGRAPHIC SUITES	22
10	6.6	MESSAGE AUTHENTICATION CODE MODE.....	22
11	6.7	SECURITY ASSOCIATION.....	22
12	6.8	SA SERVICE TYPE.....	22
13	6.9	EAP AUTHENTICATION METHODS	22
14	6.10	CERTIFICATE PROFILE.....	22
15	6.11	MULTICAST BROADCAST RE-KEYING ALGORITHM (MBRA)	22
16	7.	RADIO PROFILE.....	22
17	8.	POWER CLASS PROFILE	22
18			

LIST OF TABLES

TABLE 1. CHANGE CONTROL REVISION HISTORY	8
TABLE 2. STATUS COLUMN ENTRIES.....	11
TABLE 3. REQUIRED COLUMN ENTRIES.....	11
TABLE 4. VALUE COLUMN ENTRIES	12
TABLE 5. DUPLEXING MODE.....	13
TABLE 6. TTG/RTG	13
TABLE 7. NUMBER OF OFDM SYMBOLS IN DL AND UL SUBFRAME IN TDD MODE	14
TABLE 8. UL SOUNDING 3	15
TABLE 9. MIMO MIDAMBLE	17
TABLE 10. SSTTG/SSRTG FOR TDD.....	18

Participants

This document was developed by the WiMAX Forum® Technical Working Group (TWG).

Co-chair: Wonil Roh, Samsung

Co-chair: Vladimir Yanover, Alvarion

Vice Chair and Editor: Hassan Yaghoobi, Intel Corp.

Following is the list of TWG member companies during the development of this document.

Alcatel-Lucent, Altair Semi Conductor, Alvarion, Amicus, ArrayComm, Beceem, CISCO, Clearwire, Comcast, Comsys, Elektrobit, Ericsson, Fujitsu, Huawei Technologies, Institute for Information Industry, Intel Corporation, KDDI, Keithley, LG Electronics, Marvell, Media Tech, Mitsubishi Electric Corp, Motorola, NEC, Nextwave, Nokia, Nokia Siemens Network, Nortel Networks, PMC Sierra, Posdata, Runcom Technologies, Samsung, SEQUANS Communications, SR Telecom, Telecom Italia, Wavesat, ZTE Corporation

Revision History

Table 1. Change Control Revision History

Version	Date	Comment
v01	2009-08-01	WiMAX Forum Approved

Abstract

This document specifies the TDD-specific aspects of WiMAX Forum Mobile System Profile Release 1.5.

1. Scope

This document provides the TDD-specific aspects of the WiMAX Forum Mobile System Profile Release 1.5 specification. It serves primarily for the purpose of certification of conformant Subscriber Stations and Base Stations.

This document is complementary to WiMAX Forum Mobile System Profile Release 1.5 [2] Common Part and includes only the additional specifications required for TDD mode. At the beginning of each subsection of Sections 4 and 5, instructions are provided for inclusion of specifications relevant to WiMAX Forum Mobile System Profile Release 1.5 Common Part [2].

This specification makes use of IEEE Std 802.16 as a normative reference.

2. Normative References

The following documents contain provisions that, through reference in this text, constitute provisions of the present document. References are either specific (identified by date of publication and/or edition number or version number) or nonspecific. For a specific reference, subsequent revisions do not apply. For a non-specific reference, the latest version applies.

- [1] **IEEE Std 802.16-2009**, IEEE Standard for Local and metropolitan area networks - Part 16: Air Interface for Broadband Wireless Access Systems
- [2] **WiMAX Forum WMF-T23-001-R015v01**, WiMAX Forum® Mobile System Profile, Release 1.5 Common Part (2009-08-01)

3. Definitions

3.1 Abbreviations

3.2 Definitions of system profiles

3.3 Conventions

3.3.1 Item column

The *Item* column contains a number that identifies each description in the table.

3.3.2 Description column

The *Description* column describes in free text each respective item (e.g., parameters, timers, etc.).

3.3.3 Reference column

The *Reference* column indicates the section of the referenced standard from which the requirement for the item is derived.

3.3.4 Status column

The following notations are used in the *Status* column to indicate whether each item is mandatory or optional in the referenced standard.

Table 2. Status Column Entries

m	Explicitly shown as mandatory in the standard. Mandatory items are automatically required in the profile for implementation.
pm	Potentially mandatory. Essential for the system to perform basic operations, although not explicitly mandatory in the standard). Potentially mandatory items are required in the profile for implementation.
o	Explicitly mentioned as optional in the standard or is not explicitly optional but has capability negotiations. These items may or may not be required in the profile for implementation.
oi	Qualified option – for mutually exclusive or selectable options from a set. One or more of the options from the set shall be supported.
po	Potentially optional. Not explicitly mentioned as mandatory in the standard and not required for the system to perform basic operations.
n/a	Not applicable – in the given context, it is impossible to use the capability.

3.3.5 BS/MS Required column

The Required column indicates whether the item is required for every BS/MS to implement for WiMAX certification purposes.

Table 3. Required Column Entries

Y or y	Required for compliance to this specification.
---------------	--

N or n	Not required for compliance to this specification.
IO-NNNN	Interoperable Options for BS: Item belongs to NNNN group of features of BS equipment. More specifically <ul style="list-style-type: none"> ▪ The item is not required for compliance to this specification and ▪ The item is required for compliance with the IO-NNNN capability.
IOMS-NNNN	Interoperable Options for MS: Item belongs to NNNN group of features for which it is requested to provide testing procedure and distinct labeling of MS equipment. More specifically <ul style="list-style-type: none"> ▪ The item is not required compliance to this specification and ▪ The item is required for compliance with the IOMS-NNNN capability.
n/a	Not applicable

3.3.6 BS/MS Values column

This column indicates the specific value or range of values for each BS/MS to implement for compliance to this specification.

Table 4. Value Column Entries

xx	Set to value xx
aa - bb	Set to range aa - bb
n/a	Not applicable

3.3.7 Comment column

This column provides additional clarification and explanation.

4. PHY Profile

4.1 Profiles of BS and MS

4.1.1 System Parameters

[Add the following text and table as the content of Section 4.1.1 of Reference [2].]

The supported uplink-downlink duplexing modes are specified in Table 5.

Table 5. Duplexing Mode

Item	Description	Reference	Status	BS Required	MS Required	Comment
1	TDD	8.4.4.1	oi	Y	Y	

4.1.1.1 PHY Mode

4.1.1.2 Channel bandwidths and corresponding FFT sizes

4.1.1.3 Sampling Factor

4.1.1.4 Cyclic Prefix

4.1.1.5 Frame Configuration

4.1.1.6 TTG/RTG

Table 6. TTG/RTG

Item	Description	Reference	Status	BS Required	BS Values	MS Required	Comment
1	TTG	8.4.5.2	m	Y	296 PS for 10 MHz, 218 PS for 8.75 MHz, 376 PS for 7 MHz, 148 PS for 5 MHz and 188 PS for 3.5 MHz	n/a	5 μ s minimum specified in the referred section. The requirement is equivalent to "5 ms - (RTG+ Number of OFDM symbols x symbol duration)" where "Number of OFDM symbols" = 47 for 10 and 5 MHz, 42 for 8.75 MHz and 33 for 7 MHz.
2	RTG	8.4.5.2	m	Y	168 PS for 10 MHz, 186 PS for 8.75 MHz, 120 PS for 7 MHz, 84 PS	n/a	5 μ s minimum specified in the referred section. The requirement is equivalent to 60 μ s

Item	Description	Reference	Status	BS Required	BS Values	MS Required	Comment
					for 5 MHz and 60 PS for 3.5 MHz		for 5, 10 and 7 MHz BW and 74.4 μ s for 8.75 MHz BW.

4.1.1.7 Frame and Subframe Parameters

Parameters of Table 7 specify number of OFDM symbols in DL and UL subframes.

Table 7. Number of OFDM Symbols in DL and UL Subframe in TDD Mode

Item	Description	Reference	Status	BS Required	BS Values	MS Required	MS Values	Comment
1	Number of OFDM Symbols in DL and UL for 5 and 10 MHz BW	8.4.4.1	oi	Y	(35, 12), (34, 13), (33, 14), (32, 15), (31, 16), (30, 17), (29, 18), (28, 19), (27, 20), (26, 21)	Y	The same as BS values	
2	Number of OFDM Symbols in DL and UL for 8.75 MHz BW	8.4.4.1	oi	Y	(30, 12), (29, 13), (28, 14), (27, 15), (26, 16), (25, 17), (24, 18)	Y	The same as BS values	
3	Number of OFDM Symbols in DL and UL for 7 and 3.5 MHz BW	8.4.4.1	oi	Y	(24, 09), (23, 10), (22, 11), (21, 12), (20, 13), (19, 14), (18, 15)	Y	The same as BS values	

4.1.2 Subcarrier Allocation

4.1.2.1 DL Subcarrier Allocation

4.1.2.2 UL Subcarrier Allocation

4.1.2.3 Common SYNC Symbol

4.1.2.4 UL Sounding

[Add Table 8 to the end of Section 4.1.2.4 [2].]

Table 8. UL Sounding 3

Item	Description	Reference	Status	BS Required	MS Required	Comment
1	Two Antenna UL Sounding: Multi-Antenna Flag enabled for Cyclic Shift Separation	8.4.6.2.7	o	IO-MIM4	IOMS-MIM4	
2	Two Antenna UL Sounding: Multi-Antenna Flag enabled for Decimation Separation	8.4.6.2.7	o	IO-MIM4	IOMS-MIM4	

4.1.3 UL Control Channels**4.1.3.1 Initial Ranging****4.1.3.2 HO Ranging****4.1.3.3 Periodic Ranging****4.1.3.4 BW Request****4.1.3.5 Fast-Feedback/CQI Channel Encoding****4.1.3.6 Fast-Feedback/CQI Channel Allocation Method****4.1.4 Channel Coding****4.1.4.1 Repetition****4.1.4.2 Randomization****4.1.4.3 Convolutional Code****4.1.4.4 Convolutional Turbo Code****4.1.4.5 BTC****4.1.4.6 LDPC****4.1.4.7 Interleaving****4.1.5 H-ARQ Support****4.1.5.1 Chase Combining****4.1.5.2 Incremental Redundancy****4.1.5.3 ACK Channel**

4.1.6 Control Mechanism

4.1.6.1 Synchronization

4.1.6.2 Closed-loop Power Control

4.1.6.3 Open-loop Power Control

4.1.6.4 MS Maximum Transmission Power Limitation Control Using UCD TLV

4.1.7 Channel Measurement

4.1.7.1 CINR Measurement

4.1.7.2 RSSI Measurement

4.1.8 Modulation

4.1.8.1 PRBS (Subcarrier Randomization)

4.1.8.2 Downlink

4.1.8.3 Uplink

4.1.8.4 Pilot Modulation

4.1.8.5 Preamble Modulation

4.1.8.6 Ranging Modulation

4.1.9 MAP Support

4.1.9.1 Normal MAP

4.1.9.2 Compressed MAP

4.1.9.3 Sub-DL-UL MAP

4.1.9.4 H-ARQ MAP Message

4.1.9.5 Extended HARQ IE in the Normal MAP

4.1.9.6 DL Region Definition

4.1.10 AAS

4.1.10.1 AAS Zone Support

4.1.10.2 Supported Permutation in DL

4.1.10.3 *Supported Permutation in UL*

4.1.10.4 *AAS DL Preamble*

4.1.10.5 *AAS UL Preamble*

4.1.10.6 *Diversity MAP Scan*

4.1.10.7 *DL AAS-SDMA Pilots*

4.1.10.8 *UL AAS-SDMA Pilots*

4.1.10.9 *AAS Private MAP*

4.1.10.10 *AAS-FBCK-REQ/RSP support*

4.1.11 *STC/MIMO*

4.1.11.1 *Supported Features for DL PUSC*

4.1.11.2 *Supported Features for DL FUSC*

4.1.11.3 *Supported Features for DL Optional FUSC*

4.1.11.4 *Supported Features for DL Optional AMC*

4.1.11.5 *Supported Features for DL PUSC-ASCA*

4.1.11.6 *Supported Features in UL PUSC*

4.1.11.7 *Supported Features in UL Optional PUSC*

4.1.11.8 *Supported Features in UL Optional AMC*

4.1.11.9 *Closed-Loop MIMO*

4.1.11.10 *MIMO Feedback*

4.1.11.11 *MIMO Midamble*

[Append the table in Section 4.1.11.11 of Reference [2] with Table 9.]

Table 9. MIMO Midamble

Item	Description	Reference	Status	BS Required	MS Required	Comment
1	MIMO Midamble with 2 antennas: MIMO midamble support in STC zone with optional AMC permutation	6.3.2.3.38.6.7 , 8.4.8.5, 11.8.3.5.5 11.11 11.12	o	N	N	

2	MIMO Midamble with 2 antennas: MIMO Midamble support STC zone with PUSC permutation	6.3.2.3.38.6.7 & 8.4.8.5, 11.8.3.5.5 11.11 11.12	o	N	N	
3	MIMO Midamble with 4 antennas: MIMO midamble support in STC zone with optional AMC permutation	6.3.2.3.38.6.7 & 8.4.8.5, 11.8.3.5.5 11.11 11.12	o	N	N	
4	MIMO Midamble with 4 antennas: MIMO Midamble support STC zone with PUSC permutation	6.3.2.3.38.6.7 & 8.4.8.5, 11.8.3.5.5 11.11 11.12	o	N	N	

4.1.11.12 MIMO Soft-Handover Based Macro-diversity

4.1.11.13 H-ARQ Downlink Support for MIMO

4.1.11.14 H-ARQ Uplink Support for MIMO

4.1.12 HO Support in PHY

4.1.12.1 FBSS

4.1.12.2 MIMO Soft-handover based macro-diversity transmission

4.1.12.3 UL Macro diversity

4.2 Performance/Fidelity Requirements

4.2.1 MS Minimum Performance

4.2.1.1 SSTTG/SSRTG

Table 10. SSTTG/SSRTG for TDD

Item	Description	Reference	Status	MS Required	MS Values	Comment
1	SSTTG	8.4.4.3	m	Y	50 μs	
2	SSRTG	8.4.4.3	m	Y	50 μs	

1	4.2.1.2	<i>Max DL Concurrent Bursts</i>
2	4.2.1.3	<i>Max Bursts in DL Subframe</i>
3	4.2.1.4	<i>Max Number of Zones in DL/UL Subframe</i>
4	4.2.1.5	<i>Measurement Processes and CQI Channels</i>
5	4.2.1.6	<i>Max H-ARQ Bursts in DL/UL Subframe</i>
6	4.2.2	Transmit Requirements
7		
8	4.2.3	Receiver Requirements
9		
10	4.2.4	Frequency and Time Synchronization Requirements
11		
12		

5. MAC Profile

5.1 *Profiles of BS and MS*

5.1.1 PHS

5.1.2 CS Options

5.1.3 MAC PDU formats

5.1.4 MAC Support of PHY layer

5.1.4.1 *Feedback Mechanism*

5.1.5 Multicast connection

5.1.6 Network Entry

5.1.7 ARQ

5.1.8 MAC support for H-ARQ

5.1.9 QoS

5.1.10 Data delivery services for mobile network

5.1.11 Request-Grant mechanism

5.1.12 Neighbor Advertisement

5.1.13 Scanning and Association

5.1.13.1 *Scanning*

5.1.13.2 *Scan Reporting Type Support*

5.1.13.3 *Association*

5.1.13.4 *Association Type Support*

5.1.13.5 *HO/Scan/Report Trigger Metrics*

5.1.14 MAC layer HO procedures

5.1.15 HO Optimization

5.1.16 CID and SAID Update

1		
2	5.1.17	Fast BS Switching
3		
4	5.1.18	Macro Diversity Handover
5		
6	5.1.19	Sleep Mode
7		
8	5.1.20	Idle Mode
9		
10		
11	5.1.21	Expedited Network Re-entry from Idle Mode
12		
13		
14	5.1.22	MBS
15		
16	5.1.23	AAS
17		
18	5.1.24	MS's Network Entry issued by BS restart
19		
20	5.1.25	NSP Selection
21		
22	5.1.26	Load Balancing
23		
24	5.1.27	Location Based Services
25		
26	5.1.28	Coexistence Among WiMAX™, Wi-Fi® and Bluetooth® Networks
27		
28	5.1.29	Capacity Improvements for Feedbacks
29		
30	5.1.30	Persistent Allocation
31		
32	5.1.31	Alternative RAT Advertisement
33		

1 **5.2 Parameters**

2 **6. Security**

3 **6.1 Authorization Policy Support**

4 **6.2 PKM Version Support**

5 **6.3 PKMv2 Authorization policy support – initial network entry**

6 **6.4 PKMv2 Authorization policy support – network re-entry**

7 **6.5 Supported cryptographic suites**

8 **6.6 Message Authentication Code Mode**

9 **6.7 Security Association**

10 **6.8 SA Service Type**

11 **6.9 EAP Authentication methods**

12 **6.10 Certificate profile**

13 **6.11 Multicast Broadcast Re-keying Algorithm (MBRA)**

14 **7. Radio Profile**

15 **8. Power Class Profile**