



ARIB STD-B67

ESSENTIAL PARAMETER VALUES
FOR THE EXTENDED IMAGE DYNAMIC
RANGE TELEVISION (EIDRTV) SYSTEM
FOR PROGRAMME PRODUCTION

ARIB STANDARD

ARIB STD-B67 Version 1.0

Version 1.0 July 3, 2015

Association of Radio Industries and Businesses

General Notes to the ARIB Standards and Technical Reports

1. The copyright of this document is ascribed to the Association of Radio Industries and Businesses (ARIB).
2. All rights reserved. No part of this document may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, without the prior written permission of ARIB.
3. The establishment, revision and abolishment of ARIB Standards and Technical Reports are approved at the ARIB Standard Assembly, which meets several times a year. Approved ARIB Standards and Technical Reports are made publicly available in hard copy, CDs or through web posting, generally in about one month after the date of approval.

This document may have been further revised therefore users are encouraged to check the latest version at an appropriate page under the following URL:

<http://www.arib.or.jp/english/index.html>

Foreword

The Association of Radio Industries and Businesses (ARIB) investigates and summarizes the basic technical requirements for various radio systems in the form of “ARIB Standards”. These standards are developed with the participation of and through discussions amongst radio equipment manufacturers, telecommunication operators, broadcasting equipment manufacturers, broadcasters and users.

ARIB Standards include “government technical regulations” (mandatory standard) that are set for the purpose of encouraging effective use of frequency and preventing interference with other spectrum users, and “private technical standards” (voluntary standards) that are defined in order to ensure compatibility and adequate quality of radio equipment and broadcasting equipment as well as to offer greater convenience to radio equipment manufacturers, telecommunication operators, broadcasting equipment manufacturers, broadcasters and users.

This ARIB Standard is developed for “ESSENTIAL PARAMETER VALUES FOR THE EXTENDED IMAGE DYNAMIC RANGE TELEVISION (EIDRTV) SYSTEM FOR PROGRAMME PRODUCTION”. In order to ensure fairness and transparency in the defining stage, the standard was set by consensus at the ARIB Standard Assembly with the participation of both domestic and foreign interested parties from radio equipment manufacturers, telecommunication operators, broadcasting equipment manufacturers, broadcasters and users.

ARIB sincerely hopes that this ARIB Standard will be widely used by radio equipment manufacturers, telecommunication operators, broadcasting equipment manufacturers, broadcasters and users.

NOTE:

Although this ARIB Standard contains no specific reference to any Essential Industrial Property Rights relating thereto, the holders of such Essential Industrial Property Rights state to the effect that the rights listed in the Attachment 1 and 2, which are the Industrial Property Rights relating to this standard, are held by the parties also listed therein, and that to the users of this standard, in the case of Attachment 1, such holders shall not assert any rights and shall unconditionally grant a license to practice such Industrial Property Rights contained therein, and in the case of Attachment 2, the holders shall grant, under reasonable terms and conditions, a non-exclusive and non-discriminatory license to practice the Industrial Property Rights contained therein. However, this does not apply to anyone who uses this ARIB Standard and also owns and lays claim to any other Essential Industrial Property Rights of which is covered in whole or part in the contents of the provisions of this ARIB Standard.

ARIB STD-B67

Attachment 1
(N/A)

(selection of option 1)

Attachment 2
(N/A)

(selection of option 2)

Contents

Foreword	
Chapter 1 : General Descriptions.....	1
1.1 Objective.....	1
1.2 Scope.....	1
Chapter 2 : System parameters for EIDRTV	2
2.1 System colorimetry	2
2.2 Signal format	2
2.3 Digital representation	2

Chapter 1 : General Descriptions

1.1 Objective¹

This standard specifies the system parameters essential for the extended image dynamic range television (EIDRTV) including system colorimetry, signal format and digital representation. The signal format is characterized by opto-electronic transfer function (OETF). For the other system parameters, other television system standards may be referred to.

1.2 Scope

This standard applies to the video equipment for programme production of the extended image dynamic range television.

1 In the interest of maintaining consistency with International Standards, when an ITU-R Recommendation on Extended Image Dynamic Range Television (EIDRTV) is approved, this standard should be reviewed.

Chapter 2 : System parameters for EIDRTV

2.1 System colorimetry

The system colorimetry specified in Table 1 should be used for EIDRTV.

2.2 Signal format

The signal format specified in Table 2 should be used for EIDRTV.

2.3 Digital representation

The digital representation specified in Table 3 should be used for EIDRTV.

TABLE 1 System colorimetry

Parameter	Values		
Opto-electronic transfer characteristics before non-linear pre-correction	Assumed linear		
Primary colors and reference white ¹	Chromaticity coordinates (CIE, 1931)	x	y
	Red primary (R)	0.708	0.292
	Green primary (G)	0.170	0.797
	Blue primary (B)	0.131	0.046
	Reference white (D65)	0.3127	0.3290

¹ The colorimetric values of the picture information can be determined based on the reference RGB primaries and the reference white.

TABLE 2 Signal format

Parameter	Values
Signal format	R', G', B' or Y', C'_B, C'_R
Video level corresponding to reference white level, r	0.5
Reference non-linear transfer function (opto-electronic transfer function, OETF)	$E' = \begin{cases} r\sqrt{E} & 0 \leq E \leq 1 \\ a \cdot \ln(E - b) + c & 1 < E \end{cases}$ <p>where E is voltage normalized by the reference white level and proportional to the implicit light intensity that would be detected with a reference camera color channel R, G, B; E' is the resulting non-linear signal.</p> $a = 0.17883277, b = 0.28466892, c = 0.55991073$
Derivation of Y'	$Y' = 0.2627 R' + 0.6780 G' + 0.0593 B'$
Derivation of color difference signals	$C'_B = \frac{B' - Y'}{1.8814}$ $C'_R = \frac{R' - Y'}{1.4746}$

TABLE 3 Digital representation

Parameter	Values		
Coded signal	R', G', B' or Y', C'_B, C'_R		
Sampling lattice – R', G', B', Y'	Orthogonal, line and picture repetitive co-sited		
Sampling lattice – C'_B, C'_R	Orthogonal, line and picture repetitive co-sited with each other. The first (top-left) sample is co-sited with the first Y' samples.		
	4:4:4 system	4:2:2 system	4:2:0 system
	Each has the same number of horizontal samples as the Y' component.	Horizontally subsampled by a factor of two with respect to the Y' component.	Horizontally and vertically subsampled by a factor of two with respect to the Y' component.
Coding format	10 or 12 bits per component		
Quantization of $R', G', B', Y', C'_B, C'_R$	$DR' = \text{INT}[(219 \times R' + 16) \times 2^{n-8}]$ $DG' = \text{INT}[(219 \times G' + 16) \times 2^{n-8}]$ $DB' = \text{INT}[(219 \times B' + 16) \times 2^{n-8}]$ $DY' = \text{INT}[(219 \times Y' + 16) \times 2^{n-8}]$ $DC'_B = \text{INT}[(224 \times C'_B + 128) \times 2^{n-8}]$ $DC'_R = \text{INT}[(224 \times C'_R + 128) \times 2^{n-8}]$ <p>The n represents the bit depth of coding format. INT [X] is the function that returns the integer closest to X.</p>		
Quantization levels	10-bit coding		12-bit coding
Timing Reference	0 - 3 and 1 020 - 1 023		0 - 15 and 4 080 - 4 095
Video data	4 - 1 019		16 - 4 079
DR', DG', DB', DY'	Nominal Peak (100%)	940	3 760
	Reference White (r)	502	2 008
	Black (0%)	64	256
DC'_B, DC'_R	Nominal Peak (+50%)	960	3 840
	Achromatic (0%)	512	2 048
	Nominal Peak (-50%)	64	256

To: Secretariat of Standard Assembly Meeting of the Association of Radio Industries and Businesses
 FAX: +81-3-3592-1103 E-mail:std@arib.or.jp
 Nittochi Bldg. 11th Floor, 1-4-1 Kasumigaseki, Chiyoda-ku, Tokyo 100-0013, Japan

Communication Note of ARIB Standard-related Proposals, etc.			
ARIB Standard Name (No.)	ESSENTIAL PARAMETER VALUES FOR THE EXTENDED IMAGE DYNAMIC RANGE TELEVISION (EIDRTV) SYSTEM FOR PROGRAMME PRODUCTION		
Sections to be completed by sender			
Name:		Date	/ /
TEL:	FAX:	E-mail:	
Company name Department name			
Page / Section	(Please describe your proposal or present your questions or comments in concrete terms.)		
(Response)			Sections to be completed by secretariat
	Date of receipt	/ /	
Classification:			Ref. No. —
			Remarks

Please send your ARIB Standard-related question in this format.
 If you complete this form in English, please provide Japanese translation alongside the English.

ESSENTIAL PARAMETER VALUES FOR THE EXTENDED
IMAGE DYNAMIC RANGE TELEVISION (EIDRTV) SYSTEM
FOR PROGRAMME PRODUCTION
ARIB STANDARD
ARIB STD-B67 Version 1.0
(July 3, 2015)

Published by
Association of Radio Industries and Businesses

11F, Nittochi Building,
1-4-1 Kasumigaseki, Chiyoda-ku, Tokyo 100-0013, Japan
TEL 03-5510-8590
FAX 03-3592-1103

Printed in Japan
All rights reserved
